

## automatic submersible **SUMP PUMPS**

These leading automatic, submersible sump pumps are one-of-a-kind featuring superior performance and horsepower with a **FULL LIFETIME WARRANTY**. Whether thermoplastic or cast iron construction, these pumps are topline performers.



### FPO6000A

**3/4 HP**

**EXCLUSIVE full lifetime warranty**

#### FLOODMATE® 7000

- Automatic submersible sump or portable utility pump
- Superior pumping performance – up to 7000 gallons per hour
- Corrosion-resistant engineered resin construction
- Heavy-duty, energy efficient motor – only 7.5 amps
- Automatic or manual operation
- Replaces any existing submersible sump pump
- Features built-in check valve and 8' grounded power cord (optional 20' power cord #1513002-TSU and 20' float switch #PS217-64)
- 1-1/4" or 1-1/2" discharge pipe size
- Not for use in pond applications – see pages 16, 18 and 19 for pond and waterfall pumps

### FPSC4550A

**3/4 HP**

**EXCLUSIVE full lifetime warranty**

## **Water Cannon** series

**NEW!**

- Sump/effluent design capable of pumping dirty water with 3/8" solids
- Superior pumping performance – up to 5150 gallons per hour
- Heavy-duty cast iron and stainless steel construction – ideal for applications requiring a rugged submersible pump
- Motor equipped with automatic thermal protection and durable ball bearings
- Extremely quiet operation
- Premium mechanical shaft seal provides maximum pump life
- Automatic vertical switch – allows for basin depths/diameters of 10" or larger
- Includes by-pass float switch for automatic or manual operation
- 10' power cord, built in suction screen, and serviceable impeller
- 1-1/2" cast iron discharge
- 7 amp motor

### PERFORMANCE INFORMATION (Based on using 1-1/2" discharge pipe)

Rating	Warranty (years)	Model	HP	Switch Type	Min. Sump Diameter	Float Switch		Performance - Gallons per Hour at Discharge Head in Feet					Maximum Lift (no flow)
						On	Off	0'	5'	10'	15'	20'	
EXCLUSIVE	LIFETIME	FPO6000A	3/4	Float	12.6"	13.7"	4.7"	7000	6000	5040	3840	2340	25 ft
EXCLUSIVE	LIFETIME	FPSC4550A	3/4	Vertical	10"	6.5"	3"	5150	4700	4100	3500	2820	32 ft

### TYPICAL APPLICATION



### ACCESSORIES (sold separately, see page 10)

#### Required:

Check Valve	FP0026-10 (not required on FPO6000A)
Flood Alarm	FPW217-242
Discharge Hose Kit	FP0012-6F 1-1/4" x 24' or FP150-24 1-1/2" x 24'

#### Optional: (see page 8)

Battery Back-Up	FP1800DCC or FP2800DCC
-----------------	------------------------