

cast iron automatic submersible **SUMP PUMPS**

Flotec

Cast iron automatic submersible sump pumps are constructed of rugged, cast iron with a screened inlet. Each has an oil-cooled, high torque 115V motor with automatic overload protection.

Water Cannon™ series

FEATURES

- Automatic submersible sump pump
- Maximum pumping capacity - see performance chart below
- Heavy-duty cast iron and stainless steel construction
- 115V overload protected motor
- 10' grounded power cord
- 1-1/2" discharge pipe size
- Extremely quiet operation

FPSC3250A

1/2 HP

BEST 5 year warranty

- Maximum pumping capacity to 4680 gallons per hour
- Can be used in narrow 10" diameter sump basin
- 6.3 amp motor

NEW!



FPSC3250A
FPSC2250A



FPSC3200A

1/2 HP

BEST 5 year warranty

- Maximum pumping capacity to 4680 gallons per hour
- Can be used in 14" diameter sump basin
- 6.3 amp motor

NEW!



FPSC3200A
FPSC2200A



FPSC2250A

1/3 HP

Better 3 year warranty

- Maximum pumping capacity to 4380 gallons per hour
- Can be used in narrow 10" diameter sump basin
- 5.8 amp motor

NEW!

FPSC2200A

1/3 HP

Better 3 year warranty

- Maximum pumping capacity to 4380 gallons per hour
- Can be used in 14" diameter sump basin
- 5.8 amp motor

NEW!

PERFORMANCE INFORMATION (Based on using 1-1/2" discharge pipe)

| Rating | Warranty (years) | Model | HP | Switch Type | Min. Sump Diameter | Float Switch | | Performance - Gallons per Hour at Discharge Head in Feet | | | | | Maximum Lift (no flow) |
|--------|------------------|-----------|-----|-------------|--------------------|--------------|-----|--|------|------|------|------|------------------------|
| | | | | | | On | Off | 0' | 5' | 10' | 15' | 20' | |
| BEST | 5 | FPSC3250A | 1/2 | Vertical | 10" | 7-1/2" | 3" | 4680 | 4380 | 3840 | 3300 | 2340 | 28 ft. |
| BEST | 5 | FPSC3200A | 1/2 | Float | 14" | 13" | 5" | 4680 | 4380 | 3840 | 3300 | 2340 | 28 ft. |
| Better | 3 | FPSC2250A | 1/3 | Vertical | 10" | 7-1/2" | 3" | 4380 | 4020 | 3540 | 3000 | 1800 | 26 ft. |
| Better | 3 | FPSC2200A | 1/3 | Float | 14" | 13" | 5" | 4380 | 4020 | 3540 | 3000 | 1800 | 26 ft. |

ACCESSORIES (sold separately, see page 10)

Required:

| | |
|--------------------|---|
| Check Valve | FP0026-10 |
| Flood Alarm | FPW217-242 |
| Discharge Hose Kit | FP0012-6F 1-1/4" x 24' or FP150-24 1-1/2" x 24' |

Optional: (see page 8)

| | |
|-----------------|------------------------|
| Battery Back-Up | FP1800DCC or FP2800DCC |
|-----------------|------------------------|

TYPICAL APPLICATION

