

## sewage PUMP SYSTEM

Economical sewage pump system manufactured of durable thermoplastic construction. Ideal for basement installations, pumping below-grade toilets, and laundry facilities.



### FP400C

1 year warranty

- Includes FPSE3200A pump, 30 gallon basin and lid assembly, 2" check valve and automatic float switch.
- Handles up to 2" solids
- Maximum pumping capacity up to 5250 gallons per hour
- Multi-vane, non-clog vortex impeller
- 8' power cord
- Corrosion-resistant construction
- Grommets accept 4" PVC inlet, 2" PVC discharge and vent

### PERFORMANCE INFORMATION

Warranty (years)	Model	HP	Switch	Minimum Sump Diameter	Performance - Gallons per Hour at Discharge Head in Feet					Maximum Lift (no flow)
					0'	5'	10'	15'	20'	
1	FP400C	4/10	Float	18"	5250	3900	2550	960	-	18 ft.

## sewage/effluent PUMP ACCESSORIES



**FPW73-15**  
18" x 30",  
30 gallon sewage basin only



**FPW73-16**  
24" x 36",  
72 gallon sewage basin only



**FPW73-17**  
Sewage basin cover kit for  
FPW73-15 (includes seal kit)



**FPW73-18**  
Sewage basin cover kit for  
FPW73-16 (Includes seal kit)



**PW198-3**  
Seal kit only for FPW73-17  
and FPW73-18



**FPW212-4**  
2" heavy duty sewage  
check valve



**FP212-257**  
2" economy sewage check valve