

Submersible Sewage Pumps



ACE IN THE HOLE SERIES

Model 3963



- Automatic submersible sewage pump
- Maximum pumping capacity to 9000 gallons per hour
- Capable of handling 2"solids – ideal for basement installation, pumping below-grade toilets, laundry facilities and general dewatering
- Rugged cast-iron construction maximizes pump life
- Heavy-duty 13 amp motor with overload protection provides safe operation
- Includes 10' power cord
- 2" NPT cast iron discharge
- Easy installation, requires minimum 18" diameter sewage basin

1/2 HP
Lifetime Warranty



PITMASTER Model 2961



- Automatic submersible sewage pump
- Maximum pumping capacity to 5250 gallons per hour
- Capable of handling 2"solids – ideal for basement installation, pumping below-grade toilets, laundry facilities and general dewatering
- Durable corrosion-resistant thermoplastic construction maximizes pump life
- Energy-efficient 8.5 amp motor with overload protection provides safe operation
- Includes 10' power cord
- 2" NPT discharge
- Easy installation, requires minimum 18" diameter sewage basin

4/10 HP
1 Year Warranty



Performance

Model Number	HP	Warranty (Years)	Switch Type	Min. Sump Diameter	Gallons per Hour at Discharge Height Above Pumping Level				Max Lift No Flow
					0'	5'	10'	15'	
3963	1/2	LIFETIME	Float	18"	9000	7320	5400	2700	18'
2961	4/10	1	Float	18"	5250	3900	2550	960	18'